


Coro piano pure »air « datasheet

LED recessed spotlight with zoom optic (swivable). piano version for mounting on hollow ceilings. pure model for frameless installation. The spotlight is mounted with a separate plaster ring. Version with remote power supply unit, connection to 230 VAC mains voltage. Switching, dimming and *color tune* via Occhio air. The color temperature can be adjusted continuously between 2700–4000 K (optional 2200–3500 K).

The zoom optic can be rotated by 360° (with end-stop), swiveled by 30° and the light cone can be adjusted continuously between 25–60°.





- * cut-out and surrounding fold required for mounting; matching step grinder optionally available
- ** minimum thermal distance, installation height depending on driver

dimensions in mm

technical	data	Coro	piano	pure	»air«

properties	material	aluminium, glass, PVD coated, painted, plastic			
	turning range	360° (with stop)			
	mobility head	30°			
	weight	0.8 kg			
surface	zoom	bronze, matt gold, rose gold polished, matt silver, matt white, matt black, phantom polishe black phantom polished, dark chrome polished			
	tube	matt white, matt black			
Occhio »color tune« LED	average life time	>50.000 hrs			
	energy efficiency class	This product contains a light source of energy efficiency class F (2200–3500K) or E (2700–4000K)			
	power	LED 9W (incl. Occhio power supply unit approx. 12W, standby < 0.5W)			
	color rendering index	CRI Ra 92			
	color temperature (color consistency)	color tune: 2200–3500 K (2-step) 2700–4000 K (2-step)			
electricity	dimming	via Occhio air			
	connection	230 V AC			
	permitted operating conditions	ambient temperature 10-30°C, for indoor use only			













Occhi**o**

Coro piano pure »air« lighting effects





Z 25


directed light (approx. 25°)

optics: zoom lens

power: high color 9 W

luminous flux: 2200–3500 K 170–230 lm 2700–4000 K 200–240 lm





Z60

directed light (approx. 60°)

optics: zoom lens

power: high color 9 W

luminous flux: 2200–3500 K 320–420 lm 2700–4000 K 370–450 lm