


Mito soffitto 20 up lusso datasheet

Annular LED ceiling-mounted luminaire with ascot leather (selectable) covered, single-sided light output and a diameter of 20.5 cm. There is a choice of two lighting effects. As room lighting, ceiling (narrow) provides a concentrated, dazzling-free light beam for perfect lighting in all situations. wall to wall (wide) for installation on walls especially in halls or corridors in order to brighten up the opposite areas with targeted lighting without dazzling – wide light beam.

Version with integrated power supply unit for mounting on plaster surfaces; connection to 230 V AC mains voltage. Dimmable via trailing-edge phase-cut dimmer*; can alternatively be controlled via Occhio air. The color temperature can be preset (2700/3000/3500/4000 K) or can be continuously controlled from 2700 to 4000 K (optional 2200 to 3500 K) via Occhio air.



incl. power supply unit


dimensions in mm

technical data Mito soffitto 20 up lusso

properties	material	aluminium, steel, painted, anodised, PVD-coated, plastic, optical silicone, polyurethane, ascot leather
	weight	0.8 kg
surface	head	black phantom, phantom, rose gold, matt gold, matt white
	cover	nero, grigio, marrone, bianco
Occhio »color tune« LED	average life time	>50.000 hrs
	energy efficiency class (luminous efficiency)	G (42 lm / W)
	power	LED 20 W (incl. Occhio power supply unit approx. 23 W, standby < 0.5 W)
	color rendering index	high color; CRI Ra 95
	color temperature (color consistency)	2700–4000 K (2-step) 2200–3500 K (2-step 2200 K, 3-step 3500 K)
electricity	dimming	via trailing-edge phasect cut dimmer or Occhio air (optional)*
	connection	230 V AC
	power factor power supply ($\cos \phi 1$)	0.9
	flicker / stroboscopic effect	1 (PstLM) / 0.9 (SVM)
	permitted operating conditions	max. 30°C for indoor use only

* For a list of compatible dimmers, see www.occhio.com/dim_en, trailing-edge phasect cut dimmer and Occhio air not combinable

Mito soffitto 20 up lusso lighting effects




ceiling (narrow)

concentrated light, beam angle approx. 50°

inserts: narrow

luminous flux : high color 20 W 720 lm

UGR (4H8H) > 19 *





ceiling (wide)

wide-radiation light, beam angle approx. 80°

inserts : wide

luminous flux : high color 20 W 850 lm

UGR (4H8H) > 19 *



wall to wall (wide)

wide-radiation light, beam angle approx. 80°

inserts : wide

luminous flux : high color 20 W 850 lm


*The standardized indication of glare values (UGR value - 4H8H) is not quite significant for annular luminaires. In most real applications the result of an individual calculation is a UGR value < 19. Therefore, we recommend to carry out a calculation which can be prepared by our lighting design team (lightingdesign@occhio.de).

Occhio

control options

Control

Mito set box



sospeso / aura / sfera / volo:

COLOR (Sensor off)
adjustable color temperature (4 stages)
trailing-edge phase cut dimming possible

PRESET (sospeso / aura / volo)
adjustable color temperature (4 stages)
adjustable up / down light intensity (5 stages)

PRESET (sfera)
color temperature adjustable (4 stages)
light intensity adjustable (5 stages)

SENSOR


»touchless control« (gesture control)
switching, dimming, up / down fading*
»color tune« (color temperature continuously
adjustable) no external dimming possible

soffitto / alto / alto side / aura alta:

COLOR
adjustable color temperature (4 stages)
trailing-edge phase cut dimming possible

*not with sfera

Mito »air« box



sospeso / aura / sfera / volo:

SENSOR
»air« + »touchless control« (Bluetooth-
and gesture control)
control via »touchless control« and Occhio air app
or »air« controller

SENSOR OFF

»air«
control via Occhio air App or »air« controller
switching, dimming, up / down fading »color tune«
(color temperature continuously adjustable)



terra / largo / raggio:

»air«, »touchless control« (largo / raggio / terra)
and »body sensor« (raggio / terra) (Bluetooth- and
gesture control) control via »touchless control«,
»body sensor« and Occhio air App or »air«
controller

»ambient light control« (terra)
adjustment to ambient light

»presence sensor« (terra)
presence identification and automatically
shutdown by presence sensor

deactivation and adjustable via control
and sensor with »air« app

alto / alto side / aura alta:

»air« (Bluetooth - control)
control via Occhio air App or »air« controller
switching, dimming »color tune« (color tempera-
ture continuously adjustable), up / down fading
(aura alta)

with Mito »air« box no external dimming possible