Divo faro singolo mains voltage halogen

Ceiling luminaire - modular system consisting of body and head

Thanks to its unique modularity the Occhio head-body system delivers impressive lighting solutions for your room. For different lighting effects diverse, turnable reflector heads are available, which can be easily substituted at any time thanks to a simple plug-in mechanism. The diverse wall and ceiling boxes allow for all recessed and surface mounting options.


Ceiling luminaire Occhio Divo faro singolo consisting of

head Occhio Divo Occhio accessories

- body Occhio faro singolo different length and surfaces
 - different lighting effects and surfaces
 - different mounting options and surfaces

78 - 86 mm IP20 ⊕ (€





material

aluminium, brass, steel, glass

surface

head: chrome, matt chrome body: chrome, matt chrome

length/rotation angle

10 cm, 20 cm, 30 cm, 60 cm/355°

recommended lighting effects

B, C, E see p.2 cutsheet

light source

mains voltage halogen, operating voltage 230 V 60/70 W, B15d Eco, energy efficiency grade D, lifetime 2.000 h

luminous flux (bulb) 60 W / 980 lm, 70 W / 1180 lm

color temperature / color rendering

weight


body and reflector head max. 0,9 kg

mounting accessories

for surface or recessed mounting, see p.3 cutsheet

Divo faro singolo recommended lighting effects





Divo B reflector head for light with wide radiation to


with satinised glass, the light output varies compared to the illustrations shown

efficiency of reflector head clear glass 69%

satinised glass 66%

material / surface clear or satinised, heat-resistant glass reflector aluminium fixture matt chrome or chrome






reflector head for light with narrow radiation to one side


with satinised glass, the light output varies compared to the illustrations shown

efficiency of reflector head

clear glass 54% satinised glass 52%

material / surface clear or satinised, heat-resistant glass reflector aluminium fixture matt chrome or chrome





reflector head for light with wide radiation to one and narrow radiation to the other side

with satinised glass the light output varies compared to the illustrations shown

efficiency of reflector head

clear glass 79% satinised glass 77%

material / surface

clear or satinised, heat-resistant glass reflector aluminium fixture matt chrome or chrome

cutsheet

Occhio

Divo faro singolo Item numbers

Item number _matt chrome M _chrome C

max. 70 W mains voltage halogen B15d 20 cm 8F 11 00 _ turnable 30 cm 8F 12 00 _ 60 cm 8F 14	faro singolo			
		mains voltage halogen B15d	20 cm 30 cm	8F 11 00 _ 8F 12 00 _
halogen B15d turnable		max. 2 x 70 W mains voltage halogen B15d turnable version white track adapter	20 cm 30 cm 60 cm 10 cm 20 cm 30 cm 60 cm 10 cm 20 cm 30 cm	4F 11 00 _ M 4F 12 00 _ M 4F 14 00 _ M 4F 10 00 _ W 4F 11 00 _ W 4F 12 00 _ W 4F 14 00 _ W 4F 10 00 _ S 4F 10 00 _ S 4F 11 00 _ S 4F 12 00 _ S



Divo B		
	clear glass	8K 00 B1 M 8K 00 B1 C
	satinised glass	8K 00 B2 M 8K 00 B2 C
Divo C		
	clear glass	8K 00 C1 M 8K 00 C1 C
	satinised glass	8K 00 C2 M 8K 00 C2 C
Divo E		
	clear glass	8K 00 E1 M 8K 00 E1 C
	satinised glass	8K 00 E2 M 8K 00 E2 C



flat box				
0	_	for plastering or wall / ceiling box h 8 mm, ø 80 mm		8Z 00 00 _
spacing bo	x			
		for surface mounting h 22 mm, ø 80 mm		8Z 01 00 _
	0	with hole for external cable supply h 22 mm, ø 80 mm		8Z 03 00 _
(spacing bo	spacing box	for plastering or wall / ceiling box h 8 mm, ø 80 mm spacing box for surface mounting h 22 mm, ø 80 mm with hole for external cable supply	for plastering or wall / ceiling box h 8 mm, ø 80 mm spacing box for surface mounting h 22 mm, ø 80 mm with hole for external cable supply

 $^{^{\}star}$ also available in 1 phase track version for the same price, item no. 4F __ 00 __ 1