Divo soffitto due low voltage halogen

Ceiling luminaire - modular system consisting of body and head

Thanks to its unique modularity the Occhio head-body system delivers impressive lighting solutions for your room. For different lighting effects diverse, turnable reflector heads are available, which can be easily substituted at any time thanks to a simple plug-in mechanism. The diverse wall and ceiling boxes allow for all recessed and surface mounting options.

Ceiling luminaire Occhio Divo soffitto due consisting of

head Occhio Divo

- body Occhio soffitto due different length and surfaces
- different lighting effects and surfaces Occhio accessories
 - different mounting options and surfaces


IP20 **() (€** ▼
















material

aluminium, brass, steel, glass

surface

chrome, matt chrome body: chrome, matt chrome

length / travel

30 cm, 40 cm, 60 cm/120° 80 cm, 100 cm, 125 cm/90°

recommended lighting effect

A, B, C, E see p.2 cutsheet

light source

low voltage halogen, operating voltage 12 V max. 2 x 60 W, GY6.35, energy efficiency grade B, lifetime 4.000 h

luminous flux (bulb) 35 W / 860 lm, 50 W / 1180 lm, 60 W / 1650 lm

color temperature / color rendering

weight


body and reflector head max. 2,5 kg

mounting accessories

for surface or recessed mounting, see p.4 cutsheet external transformer necessary

Divo soffitto due recommended lighting effect





Divo AReflector head for light with open luminaire and radial distribution


with satinised glass, the light output varies compared to the illustrations shown

efficiency of reflector head clear glass 96%

satinised glass 93%

material / surface clear or satinised, heat-resistant glass reflector aluminium fixture matt chrome or chrome





Divo B

reflector head for light with wide radiation to


with satinised glass, the light output varies compared to the illustrations shown

efficiency of reflector head

clear glass 69% satinised glass 66%

material / surface clear or satinised, heat-resistant glass reflector aluminium fixture matt chrome or chrome





reflector head for light with narrow radiation to one side


with satinised glass, the light output varies compared to the illustrations shown


efficiency of reflector head clear glass 54%

satinised glass 52%

material / surface

clear or satinised, heat-resistant glass reflector aluminium fixture matt chrome or chrome





reflector head for light with wide radiation to one and narrow radiation to the other side

with satinised glass the light output varies compared to the illustrations shown

efficiency of reflector head

clear glass 79% satinised glass 77%

material / surface

clear or satinised, heat-resistant glass reflector aluminium fixture matt chrome or chrome

cutsheet

Occhio

Divo soffitto due Item numbers

Item number _matt chrome M _chrome C

soffitto due			
	max. 2 x 60 W low voltage halogen GY6.35	30 cm 40 cm 60 cm 80 cm 100 cm 125 cm	7S 32 00 _ 7S 33 00 _ 7S 34 00 _ 7S 35 00 _ 7S 36 00 _ 7S 37 00 _



Divo A		
	clear glass	8K 00 A1 M 8K 00 A1 C
	satinised glass	8K 00 A2 M 8K 00 A2 C
Divo B		
	clear glass	8K 00 B1 M 8K 00 B1 C
	satinised glass	8K 00 B2 M 8K 00 B2 C
Divo C		
	clear glass	8K 00 C1 M 8K 00 C1 C
	satinised glass	8K 00 E2 M 8K 00 E2 C
Divo E		
	clear glass	8K 00 E1 M 8K 00 E1 C
	satinised glass	8K 00 E2 M 8K 00 E2 C



cutsheet

Occhio

Divo soffitto due Item numbers

Item number _matt chrome M _chrome C



mounting transformer on site

flat box		
©	for plastering or wall/ceiling box h 8 mm, ø 80 mm	8Z 00 00 M 8Z 00 00 C
Electronic transformer max. 150 W	for mounting in cavity walls/ceilings, trailing- or leading-edge dimmable, 50 - 150 W, I 153 mm, w 54 mm, h 36 mm	7Z 00 03 T
Electronic transformer max. 105 W	for mounting in cavity walls/ceilings, trailing- or leading-edge dimmable, 35-105 W, I 107 mm, w 52 mm, h 30 mm	7Z 00 01 T
Electronic transformer max. 70 W	for mounting in flush-mounted boxes (wall/ceiling), not for verticale on ceiling, not for plastering box ceiling, trailing- or leading-edge dimmable, 20-70W, ø 53 mm, h 22 mm	7Z 00 02 T



transformer in surface mounted box			
Box due			
with 2 soffitto singolo body soffitto singolo see cutsheet ceiling lamp soffitto singolo			
	mounting version for 2x soffitto singolo NV incl. 2x electronic transformer 35-75W I 304 mm, w 88 mm, h 36 mm	matt chrome chrome bianco/chrome nero/chrome	7Z 90 2 00 M F 7Z 90 2 00 C F 7Z 90 2 00 B F 7Z 90 2 00 N F
	track version	matt chrome chrome bianco/chrome nero/chrome	4Z 90 2 00 M F 4Z 90 2 00 C F 4Z 90 2 00 B F 4Z 90 2 00 N F