

cutsheet

Occhio

1 | 5

Puro parete singolo mains voltage halogen

Wall luminaire - modular system consisting of body and head


Thanks to its unique modularity the Occhio head-body system delivers impressive lighting solutions for your room. For different lighting effects diverse, turnable reflector heads are available, which can be easily substituted at any time thanks to a simple plug-in mechanism. The diverse wall and ceiling boxes allow for all recessed and surface mounting options.

Wall luminaire Occhio Puro parete singolo consisting of

- body Occhio parete singolo - different length and surfaceces
- head Occhio Puro - different lighting effects and surfaceces
- Occhio accessories - different mounting options and surfaceces



Puro parete singolo C



Puro parete singolo E

material
aluminium, brass, steel, glass

surface
head: chrome, aluminium anodised
body: chrome, matt chrome

length / travel
20 cm, 30 cm, 40 cm, 60 cm / 120°

recommended lighting effects
A, B, C, D, E, P, Q, U see p.2 and p.3 cutsheet

light source
mains voltage halogen, operating voltage 230 V
max. 150 W, B15d Eco,
(max. 100 W for lighting effects C, D und E)
energy efficiency grade D, lifetime 2.000 h



luminous flux (bulb)
60 W / 980 lm, 70 W / 1180 lm, 100 W / 1800 lm, 150 W / 2870 lm

color temperature / color rendering
2900 K / CRI 100

weight
body and reflector head max. 1,5 kg

mounting accessories
for surface or recessed mounting, see p.5 cutsheet


Puro parete singolo recommended lighting effect



Puro A
reflectorhead for diffuse light
in two directions

efficiency of reflector head
84%



material / surface
satinised, heat-resistant glass
fixture matt chrome or chrome



Puro B
reflectorhead for diffuse light
in one direction

efficiency of reflector head
67%

material / surface
satinised, heat-resistant glass
reflector matt chrome or chrome
fixture matt chrome or chrome





Puro C
reflectorhead for directed light
in one direction

efficiency of reflector head
54%

beam angle
approx. 65°

material / surface
lense optical glass
reflector matt chrome or chrome
fixture matt chrome or chrome





Puro D
reflectorhead for directed light
in two directions

efficiency of reflector head
68%

material / surface
lense optical glass
fixture matt chrome or chrome

Puro parete singolo recommended lighting effect





Puro E
reflector head for diffuse light
in one direction and directed light
in the other direction

efficiency of reflector head
76%

beam angle
approx. 65°



material / surface
lense optical glass
satinised, heat-resistant glass
reflector matt chrome or chrome
fixture matt chrome or chrome



Puro P
reflector head for diffuse light in a symmetri-
cal direction

efficiency of reflector head
55%



material / surface
reflector matt chrome or chrome
fixture matt chrome or chrome



Puro Q
reflector head for diffuse asymmetric light in
one direction

efficiency of reflector head
52%

material / surface
reflector matt chrome or chrome
fixture matt chrome or chrome



Puro U
reflector head for diffuse symmetric light in
one direction

efficiency of reflector head
55%

material / surface
satinised, heat-resistant glass
reflector matt chrome or chrome
fixture matt chrome or chrome


cutsheet

Occhio





4 | 5

Puro parete singolo
Item numbers

Item number
_matt chrome M
_chrome C

parete singolo		
	max. 1 x 150 W mains voltage halogen B15d	
		



Puro A 	satinised glass / satinised glass	8 K 00 11 _
Puro B 	satinised glass / reflector sphere	8 K 00 12 _
Puro C 	reflector sphere / lense (max. 100 W) mit diffusor*	8 K 00 41 _
Puro D 	lense / lense (max. 100 W) with diffusor*	8 K 00 42 _
Puro E 	satinised glass / lense (max. 100 W) with diffusor*	8 K 00 44 _
Puro P 	reflector tray, symmetrical	8 K 00 21 _
Puro Q 	reflector tray, asymmetrical left version right version	8 K 00 22 M 8 K 00 22 C 8 K 00 22 M R 8 K 00 22 C R
Puro U 	satinised glass, perforated aluminium reflector	8 K 00 32 _

* Diffusor necessary for ideal light distribution when using clear mains voltage halogen B15d bulb and lens

cutsheet

Occhio

5 | 5

Puro parete singolo
Item numbers

Item number
_chrome matt M
_chrome C



flat box			
		for plastering or wall / ceiling box h 8 mm, ø 80 mm	8Z 00 00 _
spacing box			
		for surface mounting h 22 mm, ø 80 mm	8Z 01 00 _
		with hole for external cable supply h 22 mm, ø 80 mm	8Z 03 00 _
		with switch h 22 mm, ø 80 mm	8Z 04 00 _